

## JP 4327213

9/3,AB,LS/1 (Item 1 from file: 351)  
DIALOG(R)File 351:Derwent WPI  
(c) 2004 Thomson Derwent. All rts. reserv.

009302473

WPI Acc No: 1992-429882/ 199252

XRAM Acc No: C92-190959

Core-sheath type composite fibre - has polyamide core and polyphenylene sulphide sheath

Patent Assignee: TORAY IND INC (TORA )

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 4327213	A	19921116	JP 9199069	A	19910430	199252 B

Priority Applications (No Type Date): JP 9199069 A 19910430

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
JP 4327213	A		5	D01F-008/16	

Abstract (Basic): JP 4327213 A

Fibre comprises a polyamide in the core component and a modified polyphenylene sulphide in the sheath component. The modified polyphenylene sulphide is obtained with reacting 0.05-10 wt.% of carboxylic anhydride to polyphenylene sulphide. The polyamide of the core component occupies 80-25 wt.% of whole the composite fibre. Whole of the surface of the fibre is formed with above modified polyphenylene sulphide (PPS).

Esp. pref. polyamide is polycapramide and polyhexamethylene adipamide. The polyamide has relative viscosity of pref. more than 2.8, esp. pref. more than 3.0. Pref. PPS is linear having melt flow rate of 10-600. The carboxylic anhydride is e.g., maleic anhydride.

USE/ADVANTAGE - The core sheath type composite fibre is useful for an industrial fibre, esp. bag filter scrim ground fabric, motor knot braid, motor binder tape and fibre for reinforcing rubber. Since PPS fully covers the outside of the fibre, it has excellent heat resistance and chemical resistance. Since almost tension applied the fibre is received in the core component, the fibre has high strength, high elongation and excellent mechanical property.

Dwg.0/0